

## FAAC 452 MPS (MPN 790916)



Automation and Control - Automation Accessories - FAAC 452 MPS (MPN 790916)

**Base price not yet**

Sales price £84.55

Discount

[Ask a question about this product](#)

Description

**FAAC 452 MPS (MPN 790916)**

- 452 MPS control board 230v control board Can control one or two operators
- Power supply 230 V~ ( +6% -10%) - 50 Hz
- Absorbed power 10 W
- Motor max. load 800 W
- Accessories max. load 0,5 A
- Electric lock max. load 15 VA
- Operating ambient temperature -20 °C +55 °C
- Protection fuses 2
- Function logics Automatic / Semi-automatic / Stepped Safety device / Semi-automatic B/ Dead-man C / Stepped semi automatic
- Opening/closing time Programmable (from 0 to 120 s)
- Pause time 0, 10, 20, 30, 60, 120 s
- Closing leaf delay 0, 5, 10, 20 s
- Opening leaf delay 2 s (Can be disabled with the dip-switch)
- Thrust force Dip-switch adjustable on 8 levels for each motor
- Terminal board inputs Open / Open free leaf / Stop / Opening safety devices / Closing safety devices / Power supply + Earth
- Terminal board outputs Flashing lamp - Motors - 24 Vdc accessories power supply - 24 Vdc indicator-light - Fail safe - 12 Vac electric lock power supply
- Rapid connector To connect Minidec, Decoder or RP cards
- Selectable functions Logics and pause times - Thrust force - Opening and closing leaf delay - Reversing stroke -Fail safe - Closing safety devices logic - Pre-flashing
- Programming key work time learning