# FAAC 460 P




FAAC 460 P







Automation and Control - Automation Accessories - FAAC 460 P
Rating: Not Rated Yet

Ask a question about this product

Description

**FAAC 460 P Control Board**

- **Technical Specification**
- Power supply 230 V ~ (+6% -10%) - 50 Hz
- Max. absorbed power 35 W
- Max. motor load 800 W
- Accessories power supply 24 Vdc
- Max. accessories load 0.5 A

- Warning light power supply 24 Vdc
- Max. warning light load 3 W
- Temperature range -20°C +55°C
- Fuses Motors power supply Accessories power supply Logic power supply
- Mains filter Integrated in card
- Quick connector For decoding cards/RP Receiver
- Connector For FAACTOTUM and optional modules
- Terminal block outputs Motor 1 Motor 2 Flashing light Warning light power supply Accessories power supply
- Terminal block Removable
- Terminal block inputs Open Open single leaf Stop Closure safeties Opening safeties
- Operating logic Automatic
- Opening/closing time 25 seconds
- Pause time 25 seconds
- Closing leaf delay time 5 seconds
- Opening leaf delay time 2 seconds
- Accessories for 460P:
- FAACTOTUM for card programming
- GATECODER deceleration/anti-crushing safety
- Optional modules MEI (input expansion module)
- MEL1 (electric lock management 1)
- MEL2 (electric lock management 2)