

APC SURT10000XLI



APC SURT10000XLI





Computers and Embedded Systems - PC and Laptop Power Supplies - UPS (Uninterruptible Power Supply) - APC

SURT10000XLI

~~Price not listed yet~~

Sales price 1250,00 €

Discount

Tax amount

[Ask a question about this product](#)

Description

APC SURT10000XLI Smart-UPS RT 10000VA 230V

Model: SURT10000XLI

- APC Smart-UPS RT, 10000VA/8000W, Input 230V/Output 230V, Interface Port DB-9 RS-232, RJ-45 10/100 Base-T, Smart-Slot, Extended runtime model, Rack Height 6 U

Display Errors

- X - Red - general fault
- 3 - Battery Light

Battery condition

- new

Output

- Output Power Capacity 8000Watts /10000 VA
- Max Configurable Power 8000Watts /10000 VA
- Nominal Output Voltage 230V
- Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage
- Efficiency at Full Load 92%
- Output Voltage Distortion Less than 3%

- Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz user adjustable +/- 0.1
- Crest Factor 3 : 1
- Waveform Type Sine wave
- Output Connections
- (1) Hard Wire 3-wire (H N + G)
- (4) IEC 320 C13
- (4) IEC 320 C19
- (4) IEC Jumpers

Input

- BypassInternal Bypass (Automatic and Manual)
- Nominal Input Voltage230V
- Input Frequency50/60 Hz +/- 5 Hz (auto sensing)
- Input Connections
- Hard Wire 3 wire (1PH+N+G)
- Hard Wire 5-wire (3PH + N + G)
- Input voltage range for main operations 160 - 280V
- Other Input Voltages 220,240

Batteries & Runtime

- Battery Type
- Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
- Included Battery Modules 4
- Typical recharge time 2.20hour(s)
- Replacement battery cartridge RBC44
- RBC Quantity 2
- Typical Backup Time at Half Load 13.2minutes (4000 Watts)
- Typical Backup Time at Full Load 4.0minutes (8000 Watts)

Communications & Management

- Interface Port(s)
- DB-9 RS-232,RJ-45 10/100 Base-T,Smart-Slot
- Pre-Installed SmartSlot Cards AP9619

Control panel

- LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : Overload and Bypass Indicators
- Audible Alarm
- Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
- Emergency Power Off (EPO) Yes

Surge Protection and Filtering

- Filtering
- Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

- Maximum Height 432.00mm
- Maximum Width 263.00mm

- Maximum depth 663.00mm
- Rack Height 6U
- Net Weight 110.91KG
- Shipping Weight 129.09KG
- Shipping Height 552.00mm
- Shipping Width 597.00mm
- Shipping Depth 991.00mm
- Color Black
- Units per Pallet 1.00

Environmental

- Operating Environment 0 - 40C
- Operating Relative Humidity 0 - 95%
- Operating Elevation 0-3000meters
- Storage Temperature -15 - 45C
- Storage Relative Humidity 0 - 95%
- Storage Elevation 0-15000meters
- Audible noise at 1 meter from surface of unit 55dBA
- Online Thermal Dissipation 2,216BTU/hr

Conformance

- Regulatory Approvals
- C-tick, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 60950, EN 61000-3-2, GOST, VDE