


**FAAC 620 Rectangular Standard**



FAAC 620



Automation and Control - Barriers - FAAC 620 Rectangular Standard

**Rating:** Not Rated Yet

[Ask a question about this product](#)

Description

### FAAC 620 Rectangular Standard Automatic barrier

- The 620 barrier is suitable for beams up to 5m and is available in standard - rapid and super rapid versions.
- For heavy traffic applications  
Model 620 is available in standard - rapid and super rapid versions. The standard will take 5m beams and opens in 4.5 seconds with a 70% duty cycle. The rapid will open in as little as 2 seconds for 3m beams or 3 seconds for 4m beams and is for continuous use. The super rapid can open in 0.8-2.2 seconds and takes beams up to 3m with continuous duty.
- **Flexibility**  
The 620 range is equipped with electronic deceleration on opening and closing. Skirt kits are available for higher security and beams may be articulated for use inside car parks. A hinged system is also available for round breakaway beams.
- **Leading-edge technology**  
The 624 BLD control board has surface mount technology with a 2 digit display and 3 programming buttons. This allows simple setting of the operational parameters and enables the selection of a wide range of logic functions including customised logic. A standard setting is present for operating a pair of barriers working simultaneously.
- **New style round beam**  
We now offer a new style of round beam to fit the 620 barrier. The new style of beam is available in 2 - 3 - 4 and 5m lengths. The beam can be fitted with LED strip lighting as an alternative to the beam lights and skirt kits are available to suit the new beam style.